Toll barrier





For rapid toll processing

Rapid, reliable, and economical processing of road users is essential when collecting toll charges at bridges, tunnels and on roads. Toll barriers from Magnetic have been specially designed for this situation. The innovative MHTM[™] drive at the heart of the barriers is characterised by its speed, lack of maintenance and energy efficiency, and thus keeps long-term costs down. The Toll barriers can be adapted to meet individual requirements: there are four models with opening times of from 1.3–0.3 s, which can be equipped with a variety of control devices, flanges and barrier booms. All barrier boom types can be provided with swing-away flange. In the case of a collision with a vehicle, the barrier boom is released and can be manually re-engaged afterwards. This protects the barrier boom and the drive unit. There is also the optional auto-swing-away flange for the soft boom, which automatically re-engages after a collision with a vehicle.



Effective toll processing Toll barriers from Magnetic are the optimum solution for all toll applications thanks to their speed, reliability and low operating costs.



Innovative drive technology The MHTM[™] drive unit operates without maintenance, energy-efficiently and quietly. Its high torque ensures best possible operation even under extreme weather conditions.



Individual configuration

Four models, three control units, three different barrier booms – the Toll barriers can be individually adapted to your requirements. Our staff would be pleased to advise you!



Easy access to components

TOLL

Two simple hand movements suffice: easy access to the control system and drive unit by removing the hood and front panel. This increases user-friendliness and speeds up commissioning and servicing.

Toll barrier

- > Opening and closing times down to 0.3 s
- > Very low operating costs thanks to efficient and long-lived MHTM[™] drive
- > Ease-of-use and optimum accessibility thanks to well thought-out design
- > Prizewinning design: German Design Award 2014 and red dot design award 2012
- $\,>\,$ Designed for 10 million opening and closing cycles





Technical Data	Toll	Toll Pro	Toll HighSpeed	Toll HighSpeed 2
Lane width	Max. 3.0 m	Max. 3.0 m	Max. 3.0 m	Max. 3.2 m (with 2 barriers)
Opening/closing time	1.3 s	0.9 s	0.6 s	0.3 s
Power consumption	Max. 55 W	Max. 95 W	Max. 320 W	Max. 450 W
Drive technology	MHTM™	MHTM™	MHTM™	MHTM™
Voltage	100-240 V AC, 50-60 Hz			
Duty cycle	100 %	100 %	100 %	100 %
Housing dimensions (W x D x H)	315 x 360 x 1115 mm			
Enclosure rating	IP54	IP54	IP54	IP54
Temperature range	−30 to +55 °C			
Weight	Approx. 42 kg	Approx. 42 kg	Approx. 44 kg	Approx. 44 kg

ü

Features	Toll	Toll Pro	Toll HighSpeed	Toll HighSpeed 2
Standard colour	RAL 2000	RAL 2000	RAL 2000	RAL 2000
Barrier boom	3 models available	3 models available	3 models available	2 models available
Control system	3 models available	3 models available	2 models available	2 models available
Number of digital inputs	8	8	8	8
Input with test for safety light barrier/ laser scanner	1	1	1	1
Number of relay/ digital outputs	6/4	6/4	6/4	6/4
Closing speed	Adjustable	Adjustable	Adjustable	Adjustable


Control systems	MGC without loop detector	MGC with loop detector	MGC Pro
2 detector channels		1	\checkmark
Adjustable inputs/outputs			\checkmark
3 opening speeds			\checkmark

MAGNETIC AUTOCONTROL GMBH

www.magnetic-access.com

Options	Toll	Toll Pro	Toll HighSpeed	Toll HighSpeed 2
Special colours	~	~	~	~
Round boom (MicroBoom-T)	Up to 3.0 m	Up to 3.0 m	Up to 3.0 m	Up to 1.5 m
Octagonal boom (MicroBoom-S)	Up to 3.5 m	Up to 2.5 m	Up to 2.5 m	
Soft boom (MicroBoom-AT)	Up to 3.0 m	Up to 3.0 m	Up to 3.0 m	Up to 1.5 m
Swing-away flange	All booms	All booms	All booms	All booms
Auto-swing-away flange	Only soft boom	Only soft boom	Only soft boom	Only soft boom
Boom drop contact	\checkmark	~	~	~
Hood light	\checkmark	~	\checkmark	\checkmark
Key-operated switch	\checkmark	~	~	~
Radio module	\checkmark	~	\checkmark	~
Ethernet module	~	~	~	\checkmark
RS485 module	~	~	~	\checkmark
CAN module (counting)	~	~	~	~
Second detector module	✓	\checkmark	~	\checkmark
GSM module	~	~	~	~
Safety light barrier/laser scanner	~	~	~	\checkmark
Battery backup	~	~		

Dimensional drawings





Access to Progress

Magnetic stands for pioneering products – in every way. Our access control systems for vehicles or pedestrians clear the way for thousands of people every day – at car parks, toll gates, stations, airports and in buildings. Our technology is also pioneering, however: with innovative drives, intelligent control systems and well thought-out details it provides maximum safety and longevity. Are you also on the path to Magnetic?



Vehicle barriers

Access barriers Parking barriers Toll barriers Special barriers

Germany MAGNETIC AUTOCONTROL GMBH Grienmatt 20 79650 Schopfheim Phone +49 7622 695-5 Fax +49 7622 695-800 E-mail info@magnetic-germany.com

Australia

MAGNETIC AUTOMATION PTY LTD 38 Metrolink Circuit Campbellfield, VIC 3061 Phone +61 3 9339 2900 E-mail info@magnetic-oz.com

Austria


FAAC GMBH Münchner Bundesstraße 123 5020 Salzburg Phone +43 662 853395-0 E-mail at.info@faacgroup.com

Benelux countries FAAC BENELUX NV/SA Industriezone 3B 8490 Jabbeke Belgium Phone +32 50 320202 E-mail info@magnetic-benelux.com



Pedestrian gates

Turnstiles Swing gates Tripod gates Retractable gates Wing gates



Cars Trucks

Brazil

MAGNETIC AUTOCONTROL LTDA Rua Toledo Barbosa, 491 03061-000 Belenzinho São Paulo - SP Phone +55 11 5660 8500 E-mail info@magnetic-br.com

China MAGNETIC CONTROL SYSTEMS

CO., LTD No. 3 Building, No. 51 Lane 1159, Kang Qiao (East) Road Kang Qiao Industrial Zone, Shanghai Phone +86 21 68182970 E-mail info@magnetic-cn.com

France FAAC FRANCE 377 Rue Ferdinand Perrier 69808 St Priest Cedex Phone +33 4 72 21 86 89 E-mail info@magnetic-fr.com

India

MAGNETIC FAAC INDIA PVT LTD. PRS Centre Plot No. 373 to 376, 2nd Floor (West Wing) 1st Cross Street, Nehru Nagar Old Mahabalipuram Road Kottivakkam (Opp Rayala Technopark, Perungudi) Chennai 600041 Phone +91 44 421 23297 E-mail info@magnetic-india.com

Ireland NATIONAL AUTOMATION LTD Boyle Business Park, Boyle, Co. Roscommon F52 V590 Phone + 353 71 9663893

Phone + 353 71 9663893 E-mail sales@nal.ie Italy FAAC S.P.A. SOC. UNIPERSONALE

Via Calari, 10 40069 Zola Predosa (BO) Phone +39 05161724 Email.controlloaccessi@faactechnologies.com

Middle East

FAAC MIDDLE EAST FZE Dubai Silicon Oasis PO Box 54886 Dubai United Arab Emirates Phone +971 4 3724193 E-mail info@magnetic-uae.com

N. and S. America (excl. Brazil) FAAC INTERNATIONAL, INC 3160 Murell Road Rockledge, FL 32955 USA Phone +1 321 635 8585 E-mail info@magnetic-usa.com Scandinavia FAAC NORDIC AB Box 125 284 22 Perstorp Sweden Phone +46 435 77 95 03 E-mail info@magnetic-nordic.com

8060050EN_03

E-mail info@magnetic-nordic Southeast Asia

MAGNETIC CONTROL SYSTEMS

SDN. BHD No. 17, Jalan Anggerik Mokara 31/54 Taman Perindustrian Kota Kemuning 40460 Shah Alam Selangor Darul Ehsan Malaysia Phone +60 3 5123 0033 E-mail info@magnetic-malaysia.com

Spain CLEM, S.A.U.

Avda. de la Fuente Nueva, nº 12 – Nave 8–18 28703 San Sebastián de los Reyes Madrid Phone: +34 91 358 11 10 E-mail: info@clemsa.es

United Kingdom FAAC (UK) LIMITED Unit 10 The Hatch Industrial Park, Greywell Road, Mapledurwell, Basingstoke, Hampshire, RG24 7NG Phone 01256 318100 E-mail sales@faac.co.uk

